

Globe Marine - Drive Savers at a Glance

Model #	Part #	Weight (lbs/Kg)	Drive Saver OD	Drive Saver ID	Drive Saver Thickness	# Bolts	Bolt Thread	Bolt Lengths	Bolt Circle	Pilot Config	Pilot Dia	Torque Rating	Gear Box Flange Dia
1058	01-12-0330	14lbs / 6.35Kg	12 1/2in / 317.5mm	3-7/16in / 83mm	1 3/4in / 44.5mm	8	3/4-16	SHCS 2-3/4in HHCS 2-3/4in	8 3/4in / 222mm	Male / Female	5in / 127mm	4200ft-lbs / 5694Nm	10 1/2in / 266.7mm
1058PR	01-12-0350	14lbs / 6.35Kg	12 1/2in / 317.5mm	3-7/16in / 83mm	1 3/4in / 44.5mm	8	3/4-16	SHCS 2-3/4in HHCS 2-3/4in	8 3/4in / 222mm	Male / Female	5in / 127mm	6500ft-lbs / 8813Nm	10 1/2in / 266.7mm
1108	01-12-0360	14lbs / 6.35Kg	13 1/4in / 336.6mm	5-1/4in / 133mm	1 13/16in / 46mm	8	3/4-16	SHCS 2-3/4in HHCS 2-3/4in	9 1/2in / 241mm	Male / Female	6in / 152.4mm	4200ft-lbs / 5694Nm	11in / 279.4mm
353	01-12-0020	1-1/2lbs / .68Kg	4 5/16in / 109.5mm	1-5/8in / 41.3mm	11/16in / 17.5mm	3	3/8-24	SHCS 1in HHCS 1in	2 3/4in / 70mm	Male / Female	1 7/8in / 48mm	250ft-lbs / 339Nm	3 1/2in / 88.9mm
404	01-12-0040	2-1/2lbs / 1.13Kg	5in / 127mm	1in / 25.4mm	1in / 25.4mm	4	3/8-24	SHCS 1-1/4in HHCS 1in	3 1/4in / 83mm	Male / Female	2in / 50.8mm	550ft-lbs / 746Nm	4in / 101.6mm
404A	01-12-0050	2-1/2lbs / 1.13Kg	5in / 127mm	1-1/4in / 31.75mm	1in / 25.4mm	4	3/8-24	SHCS 1-1/4in HHCS 1in	3 1/4in / 83mm	Male / Female	2 1/2in / 63.5mm	550ft-lbs / 746Nm	4in / 101.6mm
404AC	01-12-0060	2-1/2lbs / 1.13Kg	5in / 127mm	1-1/4in / 31.75mm	1in / 25.4mm	4	3/8-24	SHCS 1-1/4in HHCS 1in	3 1/4in / 83mm	Adapted Male / Female	2 5/8in / 67mm	550ft-lbs / 746Nm	4in / 101.6mm
404V	01-12-0080	2-1/2lbs / 1.13Kg	5in / 127mm	1-5/8in / 41.3mm	1in / 25.4mm	4	M10 X 1.5	SHCS 35mm HHCS 35mm	3.15in / 80mm	Male / Female	2.36in / 60mm	550ft-lbs / 746Nm	4in / 101.6mm
424Y	01-12-0100	2-1/2lbs / 1.13Kg	4 1/4in / 108mm	1-5/8in / 41.3mm	1in / 25.4mm	4	M10 X 1.5	HHCS 25mm STUD 23mm	3.07in / 78mm	Male / Female	1.97in / 50mm	550ft-lbs / 746Nm	3.94in / 100mm
454	01-12-0110	2-1/2lbs / 1.13Kg	5 3/8in / 136.5mm	1-1/2in / 38.1mm	1in / 25.4mm	4	3/8-24	SHCS 1-1/4in HHCS 1in	3 3/4in / 95mm	Adapted Male / Female	2 5/8in / 67mm	570ft-lbs / 773Nm	4 1/2in / 114.3mm
4756	01-12-0420	3lbs / 1.36Kg	5 3/8in / 136.5mm	1-5/8in / 41.3mm	1in / 25.4mm	6	7/16-20	SHCS 1-1/2in HHCS 1in	3 7/8in / 98mm	Male / Female	2 1/2in / 63.5mm	675ft-lbs / 915Nm	4 3/4in / 120.7mm
4756A	01-12-0440	3lbs / 1.36Kg	4 7/8in / 123.8mm	1-5/8in / 41.3mm	1in / 25.4mm	6	7/16-20	SHCS 1-1/2in HHCS 1in	3 7/8in / 98mm	Male / Female	2 1/2in / 63.5mm	675ft-lbs / 915Nm	4 3/4in / 120.7mm
4756APR	01-12-0450	3lbs / 1.36Kg	4 7/8in / 123.8mm	1-5/8in / 41.3mm	1in / 25.4mm	6	7/16-20	SHCS 1-1/2in HHCS 1in	3 7/8in / 98mm	Male / Female	2 1/2in / 63.5mm	1600ft-lbs / 2169Nm	4 3/4in / 120.7mm
4756PR	01-12-0460	3lbs / 1.36Kg	5 3/8in / 136.5mm	1-5/8in / 41.3mm	1in / 25.4mm	6	7/16-20	SHCS 1-1/2in HHCS 1in	3 7/8in / 98mm	Male / Female	2 1/2in / 63.5mm	1600ft-lbs / 2169Nm	4 3/4in / 120.7mm
504	01-12-0130	3lbs / 1.36Kg	6in / 152.4mm	1-1/2in / 38.1mm	1in / 25.4mm	4	7/16-20	SHCS 1-1/2in HHCS 1-1/2in	4 1/4in / 108mm	Male / Female	2 1/2in / 63.5mm	675ft-lbs / 915Nm	5in / 127mm
504A	01-12-0140	3lbs / 1.36Kg	6in / 152.4mm	1-1/2in / 38.1mm	1in / 25.4mm	4	3/8-24	SHCS 1-1/4in HHCS 1in	4 1/8in / 105mm	Male / Female	2 3/4in / 70mm	675ft-lbs / 915Nm	5in / 127mm
504AC	01-12-0150	3lbs / 1.36Kg	6in / 152.4mm	1-1/2in / 38.1mm	1in / 25.4mm	4	7/16-20	SHCS 1-1/2in HHCS 1-1/2in	4 1/8in / 105mm	Male / Female	2 7/8in / 73mm	675ft-lbs / 915Nm	5in / 127mm
504APR	01-12-0160	3lbs / 1.36Kg	6in / 152.4mm	1-1/2in / 38.1mm	1in / 25.4mm	4	3/8-24	SHCS 1-1/4in HHCS 1in	4 1/8in / 105mm	Male / Female	2 3/4in / 70mm	1600ft-lbs / 2169Nm	5in / 127mm
504H	01-12-0170	3lbs / 1.36Kg	5 1/8" / 130.2mm	1-3/4in / 44.5mm	1in / 25.4mm	4	7/16-20	SHCS 1-1/2in HHCS 1-1/2in	4 1/4in / 108mm	Male / Female	2 1/2in / 63.5mm	675ft-lbs / 915Nm	5in / 127mm
504HPR	01-12-0180	3lbs / 1.36Kg	5 1/8" / 130.2mm	1-3/4in / 44.5mm	1in / 25.4mm	4	7/16-20	SHCS 1-1/2in HHCS 1-1/2in	4 1/4in / 108mm	Male / Female	2 1/2in / 63.5mm	1600ft-lbs / 2169Nm	5in / 127mm
504PR	01-12-0190	3lbs / 1.36Kg	6" / 152.4mm	1-1/2in / 38.1mm	1in / 25.4mm	4	7/16-20	SHCS 1-1/2in HHCS 1-1/2in	4 1/4in / 108mm	Adapted Male / Female	2 1/2in / 63.5mm	1600ft-lbs / 2169Nm	5in / 127mm
524Y	01-12-0200	3lbs / 1.36Kg	5 1/4in / 133.3mm	2in / 50.8mm	1in / 25.4mm	4	M10 X 1.5	HHCS 25mm STUD 23mm	3.94in / 100mm	Male / Female	2.55in / 65mm	675ft-lbs / 915Nm	4.72in / 120mm

Globe Marine - Drive Savers at a Glance

Model #	Part #	Weight (lbs/Kg)	Drive Saver OD	Drive Saver ID	Drive Saver Thickness	# Bolts	Bolt Thread	Bolt Lengths	Bolt Circle	Pilot Config	Pilot Dia	Torque Rating	Gear Box Flange Dia
554	01-12-0210	3lbs / 1.36Kg	6 1/2in / 165.1mm	1-7/8in / 47.63mm	1in / 25.4mm	4	3/8-24	SHCS 1-1/4in HHCS 1in	4 5/8in / 117mm	Male / Female	3 1/8in / 49.4mm	720ft-lbs / 976Nm	5 1/2in / 139.7mm
554PR	01-12-0220	3lbs / 1.36Kg	6 1/2in / 165.1mm	1-7/8in / 47.63mm	1in / 25.4mm	4	3/8-24	SHCS 1-1/4in HHCS 1in	4 5/8in / 117mm	Male / Female	3 1/8in / 49.4mm	1900ft-lbs / 2576Nm	5 1/2in / 139.7mm
5756	01-12-0470	5lbs / 2.27Kg	6 13/16in / 173mm	1-3/4in / 44.5mm	1 1/8in / 28.6mm	6	1/2-20	SHCS 1-1/2in HHCS 1-1/4in	4 3/4in / 121mm	Male / Female	3in / 76mm	1800ft-lbs / 2440Nm	5 3/4in / 146.1mm
5756A	01-12-0480	5lbs / 2.27Kg	6 3/8in / 161.9mm	1-3/4in / 44.5mm	1 1/8in / 28.6mm	6	1/2-20	SHCS 1-1/2in HHCS 1-1/4in	4 3/4in / 121mm	Male / Female	3in / 76mm	1800ft-lbs / 2440Nm	5 3/4in / 146.1mm
5756APR	01-12-0490	5lbs / 2.27Kg	6 3/8in / 161.9mm	1-3/4in / 44.5mm	1 1/8in / 28.6mm	6	1/2-20	SHCS 1-1/2in HHCS 1-1/4in	4 3/4in / 121mm	Male / Female	3in / 76mm	3000ft-lbs / 4067Nm	5 3/4in / 146.1mm
5756AZF	01-12-0500	5lbs / 2.27Kg	6 3/8in / 161.9mm	1-3/4in / 44.5mm	1 1/8in / 28.6mm	6	1/2-20	SHCS 1-1/2in HHCS 1-1/4in	4 3/4in / 121mm	Female / Female	3in / 76mm	1800ft-lbs / 2440Nm	5 3/4in / 146.1mm
5756PR	01-12-0520	5lbs / 2.27Kg	6 13/16in / 173mm	1-3/4in / 44.5mm	1 1/8in / 28.6mm	6	1/2-20	SHCS 1-1/2in HHCS 1-1/4in	4 3/4in / 121mm	Male / Female	3in / 76mm	3000ft-lbs / 4067Nm	5 3/4in / 146.1mm
6256PR	01-12-0540	6lbs / 2.72Kg	7 1/4in / 184.2mm	2in / 50.8mm	1 1/16in / 27mm	6	7/16-20	SHCS 1-1/2in HHCS 1-1/2in	5 3/8in / 137mm	Adapted Male / Female	3 1/4in / 82.6mm	3200ft-lbs / 4339Nm	6 1/4in / 158.8mm
7256	01-12-0550	6lbs / 2.72Kg	8 3/8in / 212.7mm	2in / 50.8mm	1 3/16in / 30.2mm	6	5/8-18	SHCS 1-3/4in HHCS 1-3/4in	6in / 152mm	Male / Female	3 3/4in / 95mm	3200ft-lbs / 4339Nm	7 1/4in / 184.2mm
7256PR	01-12-0560	6lbs / 2.72Kg	8 3/8in / 212.7mm	2in / 50.8mm	1 3/16in / 30.2mm	6	5/8-18	SHCS 1-3/4in HHCS 1-3/4in	6in / 152mm	Male / Female	3 3/4in / 95mm	4400ft-lbs / 5966Nm	7 1/4in / 184.2mm
7258ZPR	01-12-0570	8lbs / 3.63Kg	7 1/4in / 184.2mm	2in / 50.8mm	1 1/4in / 31.8mm	8	5/8-18	SHCS 1-3/4in HHCS 1-3/4in	6in / 152mm	Male / Female	3 3/4in / 95mm	3200ft-lbs / 4339Nm	7 1/4in / 184.2mm
7306Z	01-12-0580	9lbs / 4.1Kg	7 1/4in / 184.2mm	2in / 50.8mm	1 3/16in / 30.2mm	6	5/8-18	SHCS 2-1/4in HHCS 1-3/4in	6in / 152mm	Female / Female	3 3/4in / 95mm	2200ft-lbs / 2983Nm	7 1/4in / 184.2mm
8010Z	01-12-0610	9lbs / 4.1Kg	8 5/16in / 211.1mm	3-3/4in / 95.3mm	1 1/2in / 38.1mm	10	M14 X 2	SHCS 60mm HHCS 50mm	6.69in / 170mm	Male / Female	5 1/2in / 139.7mm	3300ft-lbs / 4474Nm	8.07in / 205mm
8010ZPR	01-12-0620	9lbs / 4.1Kg	8 5/16in / 211.1mm	3-3/4in / 95.3mm	1 1/2in / 38.1mm	10	M14 X 2	SHCS 60mm HHCS 50mm	6.69in / 170mm	Male / Female	5 1/2in / 139.7mm	4800ft-lbs / 6508Nm	8 1/16in / 204.8mm
8078Z	01-12-0630	9lbs / 4.1Kg	8 1/16in / 204.8mm	2in / 50.8mm	1 3/4in / 44.5mm	8	5/8-18	SHCS 2-1/4in HHCS 1-3/4in	6 11/16in / 170mm	Female / Female	5 1/2in / 139.7mm	3300ft-lbs / 4474Nm	8 1/16in / 204.8mm
8858ZPR	01-12-0660	9lbs / 4.1Kg	9 1/8in / 231.8mm	3-3/4in / 95.3mm	1 1/2in / 38.1mm	8	M14 X 2	SHCS 60mm HHCS 50mm	7.71in / 196mm	Male / Female	5 1/2in / 139.7mm	5000ft-lbs / 6779Nm	8.85in / 225mm
908	01-12-0230	14lbs / 6.35Kg	11in / 279.4mm	3in / 76.2mm	1 3/8in / 34.9mm	8	5/8-18	SHCS 2-1/4in HHCS 2-1/4in	7 1/2in / 191mm	Male / Female	6in / 152.4mm	3000ft-lbs / 4067Nm	9in / 228.6mm
908A	01-12-0250	14lbs / 6.35Kg	11in / 279.4mm	3in / 76.2mm	1 3/8in / 34.9mm	8	5/8-18	SHCS 2-1/4in HHCS 2-1/4in	7 3/4in / 197mm	Male / Female	5 1/8in / 130.2mm	3000ft-lbs / 4067Nm	9in / 228.6mm
908PR	01-12-0300	14lbs / 6.35Kg	11in / 279.4mm	3in / 76.2mm	1 3/8in / 34.9mm	8	5/8-18	SHCS 2-1/4in HHCS 2-1/4in	7 1/2in / 191mm	Male / Female	6in / 152.4mm	4900ft-lbs / 6644Nm	9in / 228.6mm
908S	01-12-0310	14lbs / 6.35Kg	9 1/8in / 231.8mm	3in / 76.2mm	1 3/8in / 34.9mm	8	5/8-18	SHCS 2-1/4in HHCS 2-1/4in	7 1/2in / 191mm	Male / Female	6in / 152.4mm	3000ft-lbs / 4067Nm	9in / 228.6mm
908SPR	01-12-0320	14lbs / 6.35Kg	9 1/8in / 231.8mm	3in / 76.2mm	1 3/8in / 34.9mm	8	5/8-18	SHCS 2-1/4in HHCS 2-1/4in	7 1/2in / 191mm	Male / Female	6in / 152.4mm	4900ft-lbs / 6644Nm	9in / 228.6mm